



คีย์ คุณสมบัติ

- True 4K HDR visual experience
- 4.2ms Ultra-Fast Input & 240Hz high refresh rate
- Warping, auto V keystone and H/V keystone for flexible installation
- 3,200 ANSI Lumens offering bright images in any environment
- Larger screen size with lower cost-per-inch




สินค้า รายละเอียด

The PX701-4K is a 3,200 ANSI Lumens high brightness 4K home projector, a great-value choice for upgrading to 4K. Take in impressive visuals in true 4K clarity supporting HDR/HLG, or upgrade your gaming experience to the next level with 4.2ms Ultra-Fast Input and 240Hz refresh rate. Project an up-to-300" big screen on any surface easier than ever with powerful warping, auto V keystone, H/V keystone and 4-corner adjustment. In addition, the energy-efficient 20,000 hours long lamp life gives it an even lower total cost of ownership than the typical lamp projector.



03

1. Power Key
2. Keypad
3. Front IR
4. Zoom/Focus Ring
5. HDMI X 2
6. AC In
7. RS-232



8. Audio Out
9. Kensington Lock
10. USB Type A(5V/1.5A)

SPECIFICATION

Projection System:	0.47" 4K-UHD
Native Resolution:	3840x2160
Brightness:	3200 (ANSI Lumens)
Contrast Ratio with SuperEco Mode:	12000:1
Display Color:	1.07 Billion Colors
Light Source Type:	Lamp
Light Source Life (hours) with Normal Mode:	6000
Light Source Life (hours) with SuperEco Mode:	20000
Lamp Watt:	203W
Lens:	F=2.0-2.05, f=15.843-17.445mm
Projection Offset:	120%+/-6%
Throw Ratio:	1.5-1.65
Optical Zoom:	1.1x
Digital Zoom:	0.8x-2.0x
Image Size:	30"-300"
Throw Distance:	1m-10.96m, (100"@3.32m)
Keystone:	H:+/-40°, V:+/-40°
Lens Shift V. Range:	Up to 20% (Digital)
Lens Shift H. Range:	Up to 20% (Digital)
Audible Noise (Normal):	31dB
Audible Noise (Eco):	28dB
Input Lag:	4.2ms
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160)
HDTV Compatibility:	720p, 1080i, 1080p, 2160P
Horizontal Frequency:	15K-135KHz
Vertical Scan Rate:	23-240Hz

INPUT

HDMI:	2, (HDMI 2.0b/ HDCP 1.4/2.2)
-------	------------------------------

OUTPUT

Audio out (3.5mm):	1
Speaker:	10W
USB Type A (Power):	1 (5V/ 1.5A)

CONTROL

RS232 (DB 9-pin male):	1
------------------------	---

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz, (AC in)
Power Consumption:	Normal: 290W, Standby: <0.5W
Operating Temperature:	0~40°C
Net Weight:	2.8kg
Dimensions (WxDxH) with Adjustment Foot:	312x222x108mm

OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Total 23 languages
---------------	---

STANDARD ACCESSORY

Power Cord:	1
Remote Control:	1
QSG:	Yes

OPTIONAL ACCESSORY

Lamp/Light Source:	RLC-126
Carry Bag:	PJ-CASE-008